

DC320R MOWER CONDITIONER
STOCK **CLEARANCE**
ONLY \$40,000 ⁺ GST

EXCLUSIVE
RR Double R
OFFER

LIMITED STOCK
& FOR A LIMITED TIME

 **NEW HOLLAND**
AGRICULTURE

STOCK

CLEARANCE*

DC320R MOWER CONDITIONER

ONLY \$40,000⁺ GST



Offer is limited to Double R ex-yard stock units only as per their current location. Enquire today; the offer is only valid for orders signed with a deposit by 30th November 2023 with full payment and delivery before 31st December 2023. Finance available through CNHIC.



DISCUTTER™ C CENTRE TRAILED MOWER

The 320R DiscCutter™ Centre trailed mower with a 3.11-metre cut is equipped with a spring floatation system, which reacts to ground pressure for uniform cutting. The centre-trailed drawbar offers the ultimate in side-to-side flexibility and operational efficiency. To protect the mower, TopSafe™ technology engages when the mower encounters obstacles, such as rocks. It is fitted with rubber chevron rollers, designed with delicate crops in mind, such as alfalfa and clover. Thanks to the gentle conditioning action, fodder value is maintained.

PRODUCTIVE GEARBOX TECHNOLOGY

The 360° gearbox has been designed to deliver tight turning performance on headlands and can turn through a full 90° circumference to draw bar, without causing any vibrations.

TOPSAFE™ SYSTEM

When working in stony ground, the TopSafe™ feature delivers outstanding performance. If the mower comes into contact with a stone or a protruding obstacle, the cutterbar is automatically lifted over the obstacle to avoid a potentially damaging collision. As a result, damage is reduced and machine life is increased. The sensitivity of this system is controlled by adjusting two springs with a dedicated tool. This enables the mower to glide freely across the ground, no matter its undulations, as well as delivering uniform stubble height and encouraging regrowth. This system does not impact on the ground pressure system.

Model	320R
Drawbar Type	Central pull
Working width (m)	3.11
Conditioner type	Rubber Chevron Rolls
Flotation type	Springs
Swath width (m)	1.2-2.0
TopSafe™ protection system ▶	●
Blade type	Twisted blades
Number of discs/blades	8/16
Number of swivel gearboxes	2
Minimum PTO Power [kW/hp(CV)]	70/94
Hydraulic remote required	1S + 1D
Power take-off	1 ³ / ₈ - 6 splines
PTO speed (rpm)	1000
Linkage category	II
Transport width (m)	3
Tyres, standard	380/55-17 FL+
Weight (kg)	2680

● Standard



*Terms and conditions: 1. This offer applies only to Double R ex-yard stock units as per their current location. 2. Order must be placed with deposit until 30th November 2023 with delivery and full payment and delivery before 31st December 2023. 3. The advertised special price is subject to change and may exclude any additional costs for delivery and set-up fees incurred. 4. Offer terms are subject to change upon 24 hours' notice. 5. Finance provided by CNH Industrial Capital Australia Pty Ltd to approved ABN business applicants and subject to credit approval.

Double R

Available at Double R: **Tamworth, Hunter Valley & Gunnedah**
www.dblr.com.au • 1800 64 3257 for your nearest Double R Branch